



# TruLaser Tube 3000 fiber

Technical data

# TruLaser Tube 3000 fiber

## ROUND TUBE

MAXIMUM OUTSIDE DIAMETER	152 mm
MAXIMUM OUTSIDE DIAMETER (OPTIONAL)	170 mm <sup>1</sup>

## RECTANGULAR PROFILE

MAXIMUM SIDE LENGTH AND OUTER CIRCLE DIAMETER	152 mm / 170 mm
---	-----------------

## MAXIMUM RAW MATERIAL LENGTH FOR AUTOMATIC LOADING

FOR LOADMASTER TUBE 6.5 M	6500 mm
FOR LOADMASTER TUBE 8.0 M	8000 mm <sup>2</sup>

## FINISHED PART LENGTH

FOR UNLOADING UNIT 3 M	3000 mm
FOR UNLOADING UNIT 4.75 M	4750 mm
FOR UNLOADING UNIT 6.5 M	6500 mm

## WORKPIECE WEIGHT

MAXIMUM PATH WEIGHT (STANDARD/OPTIONAL)	18.5 kg/m
---	-----------

## MAXIMUM RAW MATERIAL WEIGHT WITH AUTOMATIC LOADING

WITH LOADMASTER TUBE 6.5 M	120 kg
WITH LOADMASTER TUBE 8.0 M	148 kg

## LASER-SPECIFIC DATA - TRUFIBER 2001

MAXIMUM LASER POWER	2000 W
MAXIMUM MATERIAL THICKNESS, MILD STEEL	8 mm
MAXIMUM MATERIAL THICKNESS, STAINLESS STEEL	4 mm
MAXIMUM MATERIAL THICKNESS, ALUMINUM	4 mm
MAXIMUM MATERIAL THICKNESS, COPPER	3 mm
MAXIMUM MATERIAL THICKNESS, BRASS	3 mm

## LASER-SPECIFIC DATA - TRUFIBER 3001

MAXIMUM LASER POWER	3000 W
MAXIMUM MATERIAL THICKNESS, MILD STEEL	8 mm / 8 mm
MAXIMUM MATERIAL THICKNESS, STAINLESS STEEL	6 mm / 4 mm
MAXIMUM MATERIAL THICKNESS, ALUMINUM	6 mm / 4 mm
MAXIMUM MATERIAL THICKNESS, COPPER	4 mm
MAXIMUM MATERIAL THICKNESS, BRASS	4 mm

Subject to changes. The details in our offer and order confirmation are definitive.

## Footnotes

---

1 — Round tubes with a diameter of 152 mm to 170 mm can only be manually loaded.

2 — Value for extended versions (option)